SAFETY DATA SHEET

1. Identification

Product identifier MAQUAT® MQ615M

Other means of identification

Product Code 862102 10324-51 **Product registration**

number

Recommended use Quat Active (MUP) **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Mason Chemical Company **Address** 9075 Centre Pointe Drive

Suite 400

West Chester, OH 45069

United States

(513) 326-0600 **Telephone**

1-800-707-4568

E-mail sdsinfo@pilotchemical.com

Emergency phone number CHEMTREC International: 1-703-527-3887

CHEMTREC USA: 1-800-424-9300

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Acute toxicity, oral Category 4 Acute toxicity, dermal Category 4 Skin corrosion/irritation Category 1B Serious eye damage/eye irritation Category 1 **Environmental hazards** Hazardous to the aquatic environment, acute Category 1

Hazardous to the aquatic environment,

Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Harmful if swallowed. Harmful in contact with skin. Causes severe

skin burns and eye damage. Causes serious eye damage. Very toxic to aquatic life. Very toxic to

aquatic life with long lasting effects.

Precautionary statement

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly Prevention

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear

protective gloves/protective clothing/eye protection/face protection.

Material name: MAQUAT® MQ615M SDS US

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Supplemental information None

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Quaternary Ammonium Compounds, Benzyl-C12-C16-alkyldimethyl, Chlorides		68424-85-1	15 - < 25
1-decanaminium, n,n-dimethyl-n-octyl-, Chloride		32426-11-2	10 - < 20
1-octanaminium, N,n-dimethyl-n-octyl-, Chloride		5538-94-3	5 - < 10
Didecyldimethylammonium Chloride		7173-51-5	5 - < 10
Ethanol		64-17-5	5 - < 10
Other components below reportable	levels		40 - < 50

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

blindness could result.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under

observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the **General information** material(s) involved, and take precautions to protect themselves. Show this safety data sheet to

the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

media

so without risk. Use standard firefighting procedures and consider the hazards of other involved materials.

Specific methods General fire hazards Flammable liquid and vapor.

Material name: MAQUAT® MQ615M

SDS US 862102 Version #: 04 Revision date: 12-28-2022 Issue date: 06-01-2015

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components **Type** Value Ethanol (CAS 64-17-5) PEL 1900 mg/m3 1000 ppm **US. ACGIH Threshold Limit Values** Components Value Type Ethanol (CAS 64-17-5) **STEL** 1000 ppm **US. NIOSH: Pocket Guide to Chemical Hazards** Components Value Type Ethanol (CAS 64-17-5) **TWA** 1900 mg/m3 1000 ppm

Biological limit values Appropriate engineering controls

No biological exposure limits noted for the ingredient(s).

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Material name: MAQUAT® MQ615M SDS US

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or

smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Clear liquid **Appearance Physical state** Liquid. **Form** Liquid.

Color Clear, colorless to light straw

Odor Slight

Odor threshold Not available. 7.5 - 9.5 (1% soln.) pН Melting point/freezing point Not available. 201.2 °F (94 °C) Initial boiling point and boiling

range

116.6 °F (47.0 °C) Tag Closed Cup Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available. 40.2 mm Hg Vapor pressure Vapor density Not available.

0.945 Relative density

Solubility(ies)

Solubility (water) Miscible Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. 32.32 cSt @25.7°C **Viscosity**

Other information

7.89 lb/gal Density **Explosive properties** Not explosive. Oxidizing properties Not oxidizing.

VOC 5.0 - 10.0 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Material name: MAQUAT® MQ615M SDS US 4 / 11 862102 Version #: 04 Revision date: 12-28-2022 Issue date: 06-01-2015

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

decomposition temperature. Avoid temperatures exceeding the flash point. Contact with

incompatible materials.

Incompatible materials

Hazardous decomposition

products

Strong oxidizing agents.

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes severe skin burns. Harmful in contact with skin.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Harmful in contact with skin. Harmful if swallowed.

Product	Species	Test Results	
MAQUAT® MQ615M			
<u>Acute</u>			
Dermal			
LD50	Rabbit	< 2 g/kg	
Oral			
LD50	Rat	0.507 g/kg	
Components	Species	Test Results	
4 1			

1-decanaminium, n,n-dimethyl-n-octyl-, Chloride (CAS 32426-11-2)

/ 10 a 10
Dermal
Liquid
LD50

Acute

 LD50
 Rabbit
 2930 mg/kg

 LD50
 Rat
 3342 mg/kg

Oral Liquid

LD50 Rat 262 mg/kg

238 mg/kg

1-octanaminium, N,n-dimethyl-n-octyl-, Chloride (CAS 5538-94-3)

Acute Dermal

LD50 Rabbit 2930 mg/kg

Inhalation

Mist

LC50 Rat > 10 mg/l, 1 h

Oral

Liquid

LD50 Rat 262 mg/kg

238 mg/kg

862102 Version #: 04 Revision date: 12-28-2022 Issue date: 06-01-2015

Components **Species Test Results**

Didecyldimethylammonium Chloride (CAS 7173-51-5)

Acute

Dermal

Liquid

LD50 Rabbit 2930 mg/kg LD50 Rat 3342 mg/kg

Oral Liquid

Rat LD50 262 mg/kg

238 mg/kg

Ethanol (CAS 64-17-5)

Acute

Dermal Liquid

LD50 Rabbit > 15800 mg/kg

Inhalation

Vapor

LC50 Rat 51.3 mg/l, 6 Hours

Oral

LD50 Rat 6.2 g/kg

Quaternary Ammonium Compounds, Benzyl-C12-C16-alkyldimethyl, Chlorides (CAS 68424-85-1)

Acute

Dermal

Liquid

LD50 Rabbit 3413 mg/kg LD50 Rat 930 mg/kg

Oral Liquid

LD50 Rat 795 mg/kg LD50 Rat 304.5 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity No data available to indicate product or any components present at greater than 0.1% are

carcinogenic.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Not available. Not classified. Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Aspiration hazard Not an aspiration hazard.

Material name: MAQUAT® MQ615M SDS US

12. Ecological information

Ecotoxicity	Very toxic to aquatic life with long lasting effects.
-------------	---

Components		Species	Test Results
1-decanaminium, n,n-dimeth	yl-n-octyl-, Chlo	oride (CAS 32426-11-2)	
Aquatic			
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	0.032 mg/l, 96 h
Chronic			
Crustacea	NOEC	Daphnia	0.01 mg/l
1-octanaminium, N,n-dimeth	yl-n-octyl-, Chlo	oride (CAS 5538-94-3)	
Aquatic			
Acute			
Crustacea	LC50	Daphnia magna	0.1 mg/l, 48 h
Fish	LC50	Bluegill (Lepomis macrochirus)	0.032 mg/l, 96 h
		Oncorhynchus mykiss	0.35 mg/l, 96 h
Chronic			
Crustacea	NOEC	Daphnia	0.01 mg/l
Didecyldimethylammonium (Chloride (CAS 7	7173-51-5)	
Aquatic			
Acute			
Algae	EC50	Algae	0.062 mg/l, 72 h
Crustacea	LC50	Daphnia	0.057 mg/l, 48 h
Fish	LC50	Bluegill (Lepomis macrochirus)	0.032 mg/l, 96 h
		Danio rerio	0.97 mg/l, 96 h
Chronic			
Crustacea	NOEC	Daphnia	0.021 mg/l, 21 d
			0.01 mg/l, 21 d
Ethanol (CAS 64-17-5)			
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Quaternary Ammonium Con	npounds. Benzv	vI-C12-C16-alkyldimethyl, Chlorides (CAS 68	-
Aquatic	, ,	, , , , , , , , , , , , , , , , , , ,	,
Acute			
Fish	LC50	Bluegill (Lepomis macrochirus)	0.515 mg/l
Chronic			
Crustacea	NOEL	Daphnia	0.0042 mg/l
sistence and degradability	This produc	t is expected to be readily biodegradable.	

Pe

Bio

Partition coefficient n-octanol / water (log Kow)

Ethanol -0.31

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Dispose of contents/container in accordance with local/regional/national/international regulations. **Disposal instructions**

Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous

Waste Representative at the nearest EPA Regional Office for guidance.

Material name: MAQUAT® MQ615M 862102 Version #: 04 Revision date: 12-28-2022 Issue date: 06-01-2015 Local disposal regulations Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN2920

UN proper shipping name Transport hazard class(es) CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Quaternary Ammonium Compounds, Ethanol)

Class 8 Subsidiary risk 3 Label(s) 8.3

Packing group

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B2, IB2, T11, TP2, TP27 **Special provisions**

Ш

154 Packaging exceptions 202 Packaging non bulk 243 Packaging bulk

Note: Class 3 labels are not required when packages are transported domestically by rail or highway as noted in 49CFR 172.402

(a)

IATA

UN2920 **UN** number

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Quaternary Ammonium Compounds, Ethanol) **UN proper shipping name**

Transport hazard class(es)

Class 8 3 Subsidiary risk Ш Packing group **Environmental hazards** Yes **ERG Code** 8F

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN2920

CORROSIVE LIQUID, FLAMMABLE, N.O.S. (Quaternary Ammonium Compounds, Ethanol), **UN proper shipping name**

MARINE POLLUTANT

Not established.

Transport hazard class(es)

8 Class Subsidiary risk 3 Packing group Ш **Environmental hazards**

Marine pollutant Yes **EmS** F-E, S-C

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Material name: MAQUAT® MQ615M 862102 Version #: 04 Revision date: 12-28-2022 Issue date: 06-01-2015



IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

CERCLA (Superfund) reportable quantity, lbs

Ethanol: 100

Pilot Chemical does not provide Proposition 65 information on our safety data sheets. Proposition **California Proposition 65**

65 statements are available upon request by contacting reginfo@pilotchemical.com.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication **US federal regulations**

Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) categories

Skin corrosion or irritation

Serious eye damage or eye irritation

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

862102 Version #: 04 Revision date: 12-28-2022 Issue date: 06-01-2015

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethanol (CAS 64-17-5) Low priority

FIFRA Information This chemical is a pesticide product registered by the Environmental Protection Agency and is

subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Listed below is the hazard information as required on

the pesticide label.

Signal word DANGER

KEEP OUT OF REACH OF CHILDREN

Hazard statement Corrosive. Causes irreversible eye damage and skin burns. May be fatal if swallowed, absorbed

through skin or inhaled. Do not get in eyes, on skin or on clothing. Do not breathe vapor or spray mist. Wear a NIOSH approved respirator with an organic vapor (OV) cartridge with a combination N, R,or P filter (NIOSH approval number prefix TC-84A). Wear goggles or face shield, chemical resistant gloves and protective clothing when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove

contaminated clothing and wash before reuse.

International Inventories

Country(s) or region On inventory (yes/no)* Inventory name Australia Australian Inventory of Chemical Substances (AICS) No Canada Domestic Substances List (DSL) Yes Canada Non-Domestic Substances List (NDSL) No China Inventory of Existing Chemical Substances in China (IECSC) Yes European Inventory of Existing Commercial Chemical Europe Yes Substances (EINECS)

Europe European List of Notified Chemical Substances (ELINCS)

Japan Inventory of Existing and New Chemical Substances (ENCS)

Korea Existing Chemicals List (ECL)

New Zealand New Zealand Inventory

Philippines Philippine Inventory of Chemicals and Chemical Substances

Yes

(PICCS)

TaiwanTaiwan Chemical Substance Inventory (TCSI)YesUnited States & Puerto RicoToxic Substances Control Act (TSCA) InventoryYes

16. Other information, including date of preparation or last revision

 Issue date
 06-01-2015

 Revision date
 12-28-2022

Version # 04

HMIS® ratings Health: 3

Flammability: 2 Physical hazard: 0

NFPA ratings Health: 3

Flammability: 2 Instability: 0

Material name: MAQUAT® MQ615M

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

The Pilot Chemical Corp. product referred to in this document is sold pursuant to Pilot Chemical Corp.'s Standard Terms and Conditions ("Terms"); however, the information contained in this document shall not be considered part of said Terms. Although the information is believed to be accurate and reliable as of the date compiled, PILOT CHEMICAL CORP. MAKES NO GUARANTEE, REPRESENTATION, OR WARRANTY, EXPRESS OR IMPLIED, REGARDING THE ACCURACY, RELIABILITY, SUFFICIENCY, SUITABILITY, MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OF ANY INFORMATION IN THIS DOCUMENT OR THE PRODUCT TO WHICH THIS DOCUMENT RELATES. Users should make their own investigations, tests and determinations as to the information's completeness and the product's suitability for their particular purposes. It is the user's responsibility to ensure that all activities comply with applicable laws. Pilot Chemical Corp. makes no warranty or representation that the information or product may be used without infringing the intellectual property rights of Pilot Chemical Corp. assumes no liability for its use.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.