

Surfactants, Quats, and Specialty Chemistries

www.pilotchemical.com 9075 Centre Pointe Dr. • Suite 400

MAQUAT® MQ624M PRODUCT DATA SHEET

PDS 862101.3.ACTIVE.06172024

PRODUCT DESCRIPTION

Maquat® MQ624M is a blend of alkyl dimethyl benzyl ammonium chloride, ADBAC, and dialkyl dimethyl ammonium chloride, DDAC, compounds in a hydroalcoholic solution. Maquat® MQ624M is an EPA-registered manufacturing use product (MUP).

EPA REG. NO.

10324-52

CAS# 7173-51-5

ACTIVE INGREDIENTS

Alkyl (50% C14, 40% C12, 10% C16) dimethyl benzyl ammonium chloride

CAS# 68424-85-1

Octyl decyl dimethyl ammonium chloride

CAS# 32426-11-2

Dioctyl dimethyl ammonium chloride

CAS# 5538-94-3

Didecyl dimethyl ammonium chloride

12.00 wt.%

Total: 80.00 wt.%

TYPICAL PROPERTIES

Appearance at 25°C Clear, light straw liquid % Active Quaternary (MW: 342), wt. % 80.0 Free Amine + Free Amine HCl, wt. % < 4.0 Ethanol, wt.% 8.0 - 15.0pH (10% Solution) 6.0 - 9.0< 200 Color (as is), APHA Density, lbs./gal. 7.61 - 7.7847°C (116.6°F) Flash Point (Tag Closed Cup) **Freezing Point** -20°C (-4°F) Shelf life 2 years

APPLICATIONS

Maquat® MQ624M is a US EPA-registered manufacturing use product (MUP) which limits its use to registered end use products (EUP) like but not limited to sanitizers, disinfectants and other FIFRA regulated applications. Formulators using this product are responsible for providing data for the EPA registration of their formulated products. Refer to the EPA master label for full list of antimicrobial formulation options.

ADVANTAGES

Mason Chemical uses the highest quality tertiary amine in the manufacture of Maquat® MQ624M. The high purity of the starting material delivers a consistent, low color and odor, high quality product that can be differentiated into consistent, high quality end-use products.

Mason Chemical Company is a listed supplier of alkyl dimethyl benzyl ammonium chloride (ADBAC/BKC (C12-C16)), CAS No. 68424-85-1, and didecyldimethylammonium chloride (DDAC (C8-10)), CAS No. 68424-95-3, on the Article 95 List. The combination of these actives is approved for product types 1, 2, 3, 4, 10, 11 and 12.

STORAGE & HANDLING

Refer to and follow the guidelines in the Safety Data Sheet (SDS) available from Mason Chemical Company for information on the safe use, handling, and disposal of this product. Mason Chemical recommends that Maquat® MQ624M should be stored in sealed containers and kept at temperatures not lower than 35°F nor higher than 120°F. Avoid overheating or freezing. If material becomes frozen it should be heated gently and stirred to ensure it is homogeneous before use. Maquat® MQ624M is not damaged by freezing.

PACKAGING

Maquat® MQ624M is available in 410 lb. poly. drum, 2000 lb. poly. tote and bulk quantities.

See additional product information at www.pilotchemical.com

The information and suggestions given are drawn from data we believe to be reliable, but in all cases, the user should check and confirm the suggestions and results in his own use before proceeding further. None of the suggestions or recommendations constitute freedom from any patents that may be existent in the field or be issued.